



Essential SmartBright G4 LED Floodlight BVP150

BVP150 LED9/CW PSU 10W SWB G2 GM

950 lm – 10 W – 6500 K

The Essential SmartBright G4 LED floodlight comes in a compact and sturdy design. Lightweight, with a robust die-cast aluminum housing and corrosion-proof coating, it's suitable for general outdoor applications. Plus, with a higher efficacy than the previous generation, it also saves more energy.

Product data

General information		Power factor (min.)	
Lamp colour code	865 cool daylight	0.9	
Driver included	Yes	Controls and dimming	
Optical cover/lens type	G [Glass]	Dimmable	No
Control interface	-	Mechanical and housing	
Connection	Flying leads/wires	Housing material	Aluminium die-cast
Cable	Cable 0.3 m without plug	Optical cover/lens material	Tempered glass
Protection class IEC	Safety class I (I)	Overall length	107 mm
CE mark	-	Overall width	102 mm
Operating and electrical		Overall height	28 mm
Input Voltage	220-240 V	Effective projected area	0.03 m²
Input frequency	50 or 60 Hz	Colour	Black
Inrush current	0.31 A	Dimensions (height x width x depth)	28 x 102 x 107 mm


Essential SmartBright G4 LED Floodlight BVP150

Approval and application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	950 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	95 lm/W
Lamp colour temperature	6500 K
Colour Rendering Index	>80
Initial chromaticity	(0.313, 0.337) SDCM <6
Initial input power	10 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-40 to +50 °C

Product data	
Full product code	871951453252699
Order product name	BVP150 LED9/CW PSU 10W SWB G2 GM
EAN/UPC – product	8719514532526
Order code	911401830283
SAP numerator – quantity per pack	1
Numerator – packs per outer box	36
SAP material	911401830283
Net Weight (Piece)	0.300 kg



Dimensional drawing



BVP150							
	10W	20W	30W	50W	70W	100W	150W
A	107	141	188	220	273	320	382
B	99	122	155	175	202	246	289
C	29	27	28	30	33	37	40
a	45	75	100	125	125	160	200
b	5	5	6	8,5	8,5	8,5	10,5
c	5,5	5,5	6,5	9	9	9	11

BVP150 LED9/CW PSU 10W SWB G2 GM

